

PRODUCT DATA SHEET



Characteristic	Description
General	
Product Name	TRAKMARK CR
Product Type	Chlorinated Rubber Road Marking Paint
Colour	White / Yellow / Red / Blue / Green / Black
Specification	APAS 0041/2 V2 – Class II Conformity
Application	Brush and /or roller application
Physical Characteristics	
Specific Gravity	1.4 – 1.5 gm / cc
Flash Point	Below 23 °C
% Solid	60% Min
Coverage	Approx. 2.7 sqm per litre @ 350 microns WFT
Packaging	
20 Ltr Standard Packaging.	
Storage	
Shelf Life is approx. 12 Months from Manufacturing subject to the material being stored in moisture-free, dry conditions without opening the packaging.	
Areas of Application	
Concrete Kerbs & Crash Barriers	

- Airfield Markings
- Parking Lots
- Temporary Horizontal Markings

Application Safeguards

- Mechanical mixing of contents recommended before use.
- The surface to be marked shall be clear of dirt, dust, debris.
- Any curing compounds / putty / previous surface coatings must be stripped off prior to application
- New Concrete / Asphalt should be allowed to cure for a minimum 20 days to maximize adhesion and durability
- Ensure surface ambient temperature is more than 10°C
- If required paint can be thinned with 5% thinner.

Safety Recommendations

- Store in cool dry environment
- Avoid contact with eatables. If ingested seek immediate medical attention.
- Recommended disposal of empty buckets as per good engineering practices and environmental policies

Post Application Care

For best results ensure traffic is not allowed on the road for a minimum duration of 1 hour after application and complete drying of material.