

ISO 9001 & ISO14001 Certified Manufacturer

PRODUCT DATA SHEET



Characteristic	Description
General	
Product Name	TRAKMARK SR
Product Type	Solvent Base Road Marking Paint
Colour	White / Yellow / Red / Blue / Green / Black
Specification	APAS 0041/2 V2 – Class II Conformity
Application	Brush and /or roller application
Physical Characteristics	
Viscosity at 30 °C	75 ± 5 kU
Density	1.1 – 1.2 Kg / cc
% Solid	> 60%
VOC	≤ 450 gm / ltr
Flash Point	> 14 C
Coverage	2.1 – 2.5 m ² / Ltr at WFT 400 Micron
Packaging	
20 Ltr Standard Packaging.	
Storage	
Shelf Life is approx. 12 Months from Manufacturing subject to the material being stored in moisture-free, dry conditions without opening the packaging.	
Areas of Application	
Concrete Kerbs & Crash Barriers	

ISO 9001 & ISO14001 Certified Manufacturer

- Airfield Markings
- Parking Lots
- Temporary Horizontal Markings

Application Safeguards

- For retro reflectorization it is recommended to apply 400 ± 25 micron WFT and glass beads spreading 250 – 300 gm / Sqm
- Mechanical mixing of contents recommended before use.
- The surface to be marked shall be clear of dirt, dust, debris.
- Any curing compounds / putty / previous surface coatings must be stripped off prior to application
- New Concrete / Asphalt should be allowed to cure for a minimum 20 days to maximize adhesion and durability
- Ensure surface ambient temperature is more than 10°C

Safety Recommendations

- Store in cool dry environment
- Avoid contact with eatables. If ingested seek immediate medical attention.
- Recommended disposal of empty buckets as per good engineering practices and environmental policies

Post Application Care

For best results ensure traffic is not allowed on the road for a minimum duration of 1 hour after application and complete drying of material.