

PRODUCT DATA SHEET



Characteristic	Description
General	
Product Name	TRAKMARK WR
Product Type	Water Based Acrylic Resin Paint
Colour	White / Yellow / Red / Blue / Green / Black – Matt Finish
Specification	IS 164
Application	Airless Spray / Roller / Brush
Physical Characteristics	
Drying Time	5 – 10 Minutes Touch Dry
Consistency	Smooth & Uniform
Viscosity at 30 °C	> 85 kU
Minimum Thickness	100 Micron
Mass in Kg / Ltr	1.4 ± 0.1 Kg / Ltr
Coverage	2.1 – 2.5 m ² / Ltr at WFT 200 Micron
Packaging	
20 Ltr Standard Packaging	
Storage	
Shelf Life: 12 Months from Manufacturing subject to the material being stored in moisture-free, dry conditions without opening the packaging.	
Areas of Application	
- Concrete Kerbs & Crash Barriers - Airfield Markings - Parking Lots - Temporary Horizontal Markings	
Application Safeguards	

ISO 9001 & ISO14001 Certified Manufacturer

- The surface to be marked shall be clear of dirt, dust, debris.
- Any curing compounds / putty / previous surface coatings must be stripped off prior to application
- New Concrete / Asphalt should be allowed to cure for a minimum 20 days to maximize adhesion and durability
- Ensure surface ambient temperature is more than 10°C
- Use Potable water for dilution

Safety Recommendations

- Store in cool dry environment
- Avoid contact with eatables. If ingested seek immediate medical attention.
- Recommended disposal of empty buckets as per good engineering practices and environmental policies

Post Application Care

For best results ensure traffic is not allowed on the road for an ideal duration of 1 hour after application and complete drying of material.